

T Series | LK11T | LK13T | LK15T | LK17T | LK21T | LK26T

TOW TRACTOR

COST EFFECTIVE. MAXIMUM PERFORMANCE.



Liftking's newly redesigned T Series Tow Tractor provides a reliable and cost-effective alternative for the manufactured housing industry. Designed to maximize performance and up-time, taking full advantage of Liftking's 50 years of experience in providing our customers with quality products they can count on.

- 4WD standard on all models with push button selection for 2WD operation.
- Full Powershift transmission available for higher torque rating and smoother operation.
- Optional foam filled and solid tires provide stable operation on all terrains.

SPECIFICATION	LK11T42	LK13T42	LK15T42	LK17T42	LK21T42	LK26T42
Towing Capacity (lbs) Using Standard 2-5/16" ball	11,500	13,500	15,500	17,500	21,500	26,500
Length	162"		166"	181"		188"
Height, Overhead Guard	102.5"					
Width	90.5"					
Wheelbase	86"			101"		108"
Lift Height	36" (9.5" to 45.5" - from top of hitch ball)					
Side Shift, Mast	6" Total					
Turning Radius Between Curbs	15'			16.5'		17.5'
Ground Clearance	12"					
Travel Speed (Unloaded)	19 mph (30 kph)					
Weight (lbs)	15,000	16,500	18,280	22,460	23,540	24,620

Engine	Perkins 854F-E34T, 55.4 kW, 74HP
Transmission	Soft-shift Powershuttle.
Optional	Electronic Powershift (standard on LK17T and up).
Axle, Front	Oscillating Drive/Steer with tight turn angle. Axle disconnect by Pushbutton.
Axle, Rear	Rigid Drive with HD Planetary Hubs.
Brakes, Service	Submerged Multi-Disc, Oil Cooled.
Brakes, Parking	Hand operated, Dry Disc.
Tires, Front	14.0 x 17.5
Tires, Rear	16.9x24 (up to LK 15T), 15.5x25 (LK17T and up).



Standard Equipment

4 wheel drive, 2 wheel steer • 36" Lift Stroke with heavy duty ball hitch • Heavy Duty Clearview Roller Mast with Dual Lift Cylinders • Hydraulic Mast side-shift • Oil Cooled Submerged Disc Brakes • Manual dry-disc parking brake • Power Steering • Soft-shift Powershuttle Transmission (Powershift on LK17T and up) • Limited Slip Differential • Tier 4 Turbo Diesel Engine • Block heater • LED Headlights, tail lights, reverse lights, and turn signals • External side view mirrors • Reinforced Overhead Guard • Wide-grip Handrails • Extra wide steps • Solid steel fenders • Lift-off doors (closed cab) • High visibility paint with black trim • Electric Horn and automatic Backup alarm • Tilt steering column with anti-restart ignition and neutral safety interlock • Adjustable all-weather suspension seat with arm rests and retractable safety belt • FOPS Operator compartment • Full gauge package: engine oil pressure gauge, fuel gauge, tachometer, hourmeter, and warning lights • Lockable sliding engine hood, fuel and hydraulic caps • High-mount air intake with pre-cleaner • Operator, maintenance and illustrated parts manuals • 1 Year 2000 hours limited warranty (2 year engine warranty).

Optional Equipment

Powershift electronic transmission (standard on LK17T and up) • Foam filled and solid tires • Extra wide mirror package • Adjustable height Strobe Light • Additional lighting • Tinted Windows • Adjustable Sunvisor • 4 Wheel Brakes • Power Assisted Brakes • Deadman seat • Safety-Start Seatbelt • Heated Mirrors • Cold Weather Package • 12V Outlet • CD /Radio • Enclosed all weather operator compartment with HD heater, sliding windows, wipers • ROPS Operator compartment • Air Conditioning • Air ride suspension seat with arm rests and retractable safety belt • Contact dealer for other options.

Liftking reserves the right to make changes in specifications shown, herein, and improvements, or discontinue manufacture at any time without notice or obligation. The information contained herein is general in nature and is not intended for specific application purposes.



Liftking reserves the right to make changes in specifications shown, herein, and improvements, or discontinue manufacture at any time without notice or obligation. The information contained herein is general in nature and is not intended for specific application purposes.

7135 Islington Avenue, Woodbridge, Ontario. L4L 1V9
Tel: 905-265-3965 | Fax: 905-851-6396