

MC Series | LK6MC | LK8MC





Let Us Do The Heavy Lifting

If your success depends on the efficient and effective lifting of heavy loads on any job site, then you can count on the complete line of Liftking forklifts to perform above and beyond the call of any construction project. Liftking has more than 50 years of expertise in designing, developing and manufacturing material handling equipment to withstand the toughest conditions.

Liftking's Newest MC Series

is compact and efficient, for when you don't need or want a full-size forklift. Easy maneuverability, great visibility, fuel efficient, and easy to transport are just some of the advantages of going small. By using proven components and a simple yet effective design, the MC Series was conceptualized from the beginning to perform more with less.



- Tier 4 Diesel Mistubishi
- Hydraulic transmission with electric power shifter
- Industrial pneumatic tires
- · Compact size with high road speed
- Ergonomically designed cab
- 2-wheel steer with tight turning radius
- LED lighting



Tight Turn Radius





Tier 4 Diesel Engine





Full Floating Cab



Clear View Mast

| SPECIFICATION | | LK6MC | LK8MC | |
|-----------------------------------------------|------------|-----------------------------------------|---------------|--|
| Lift capacity at 24 inch (600 mm) load center | lbs (kgs) | 6000 (2720) | 8000 (3630) | |
| Lifting height | | From 8 ft to 21 ft (2700 mm to 6500 mm) | | |
| Mast tilt angle F/R | deg. | | 10 / 12 | |
| Overall length (without forks) | in (mm) | 120 (3066) | 121 (3081) | |
| Overall width | in (mm) | 57 (1450) | 63 (1600) | |
| Wheelbase | in (mm) | 74 (1880) | | |
| Height to top of overhead guard | in (mm) | 89 (2256) | 89.5 (2276) | |
| Ground clearance (at rear angle) | in (mm) | 8.6 (219) | | |
| Turning radius | in (mm) | 123 (3120) | | |
| Weight | lbs (kgs) | 10,650 (4830) | 12,225 (5545) | |
| Travel speed | mph (Km/h) | 12 (19) | 11.5 (18) | |
| Max. Gradability (unladen/laden) | % | 50 | 45 | |
| Tire, Front | | 12-16.5-12PR | 14-17.5L-14PR | |
| Tire, Rear | | 10.0/75-15.3 | | |
| Battery Voltage/Capacity | V/Ah | 12/90 | | |
| Transmission Type | | Hydrostatic | | |
| Engine, Diesel | | Mitsubishi 3.3L, Tier 4 | | |
| Engine Power | HP/kW | 34 (46) @ 2300RPM | | |

Liftking reserves the right to make changes in specifications shown, herein, and improvements, or discontinue manufacture at any time without notice or obligation. The information contained herein is general in nature and is not intended for specific application purposes.

Toronto, Canada Tel: 905-265-3965 | Fax: 905-851-6396